

Enertex Power Link 261



BATTERY PARAMETERS	ENERTEX POWER LINK 261
Battery Configuration	260S1P
Battery Nominal Voltage / Capacity	832V / 314Ah
Battery Energy	261.25 kWh
Cell Type / C-Rate	Lithium Ferro Phosphate (LFP) Prismatic Type @ 0.5C
Cell Nominal Voltage / Capacity	3.2V / 314Ah
Depth of Discharge (DoD)	95%
DC Operating Voltage Range	702V to 936V
Battery Cycle Life	>10,000 Cycles
Maximum Charge / Discharge Current	130.5A
Battery Dimension (L×W×H)	1450mm × 1350mm × 2400mm
Thermal Management	Advance Intelligent Liquid Cooling
Operating Temperature Range – Charging	0°C to 50°C (<85% RH) – Above 45°C Derating
Operating Temperature Range – Discharging	-20°C to 60°C (<85% RH) – Above 45°C Derating
Working Altitude	<2000 mtr
Weight	<3 Tons
SPECIAL BATTERY PARAMETERS	
Communication Interface	RS485 / CAN / ETH / Dry Contact
Control & Communication	SCADA for Central Control & Monitoring Communication Standard Industrial Protocols
Fire Suppression System	Temperature & Smoke Detector, Aerosol, Water Fire Interface
Protection Class (IEC 60529)	IP55
Anti-Corrosion Degree	C4
System Designed Service Life	10 Years (with RTE degradation)
CERTIFICATIONS	
Battery Cell	IEC 62619
Battery Pack	UN 38.3
Battery Rack	EN 62477-1, IEC 63056
System	EN IEC 61000-6-2/4